Method of voice recognition with automatic correction

The present invention relates to a method of voice recognition with automatic correction in voice
5   recognition systems with constrained syntax, that is to say the recognizable phrases lie in a set of determined possibilities. This method is particularly suitable for voice recognition in noisy surroundings, for example in the cockpits of civil or fighter aircraft, in
10 helicopters or in motoring.

Numerous works in the field of voice recognition with constrained syntax have made it possible to obtain recognition rates of the order of 95%, doing so even in
15 the noisy environment of a fighter aircraft cockpit (approximately 100-110 dBA around the pilot's helmet). However, this performance is not sufficient to make voice command into a primary command medium for parameters that are critical from the flight safety
20 point of view.

A strategy used consists in submitting the critical commands to a validation of the pilot, who verifies through the phrase recognized that the right values
25 will be assigned to the right parameters ("primary feedback"). In case of error of the recognition system – or pilot enunciation error – the pilot must say the whole phrase again, and the probability of error in the recognition of the phrase enunciated again is the same.
30 Thus for example, if the pilot says "Select altitude two five five zero feet", the system performs the recognition algorithms and provides the pilot with visual feedback. By envisaging the case where an error occurs, the system will for example propose "SEL ALT 2
35 5 9 0 FT". In a conventional system, the pilot must then enunciate the whole phrase again, with the same probabilities of error.

AMENDED SHEET

An error correction system which is better in terms of recognition rate consists in having the pilot enunciate a correction phrase which will be recognized as such.

5 For example, returning to the above example, the pilot may say "Correction third digit five". However, this procedure increases the pilot's workload in the recognition method, this being undesirable.

10 Known from the prior art, see for example US-A-6 141 661, is a method of voice recognition of an identifier from among a prerecorded set of identifiers, in which if a first identifier has been recognized and then invalidated by the user, the voice recognition is

15 repeated, deleting the first identifier from said set. This method cannot be applied however to the voice recognition of phrases, which form too large a number of combinations to be prerecorded.

20 The invention proposes a method of voice recognition which implements automatic correction of the phrase enunciated making it possible to obtain a recognition rate of close to 100%, without increasing the pilot's load.

25

Accordingly, the invention relates to a method of voice recognition of a speech signal uttered by a speaker with automatic correction, comprising in particular a step of processing said speech signal delivering a

30 signal in a compressed form, a step of recognizing patterns so as to search, on the basis of a syntax formed of a set of phrases which represent the set of possible paths between a set of words prerecorded during a prior phase, for a phrase of said syntax that

35 is the closest to said signal in its compressed form, and characterized in that it comprises

- the storage (16) of the signal in its compressed

AMENDED SHEET

form,

-      the generation (17) of a new syntax (SYNT2) in
       which the path corresponding to said phrase
       determined during the earlier recognition step is
5   precluded,

-      the repetition of the step of recognizing patterns
       so as to search, on the basis of the new syntax,
       for another phrase that is the closest to said
       stored signal.

10

Other advantages and characteristics will become more
clearly apparent on reading the following description,
illustrated by the appended figures which represent:

15   -   figure 1, the basic diagram of a voice recognition
            system of known type;

     -      figure 2, the diagram of a voice recognition
            system of the type of that of figure 1
20   implementing the method according to the
            invention;

     -      figure 3, a diagram illustrating the modification
            of the syntax in the method according to the
25   invention.

In these figures, identical elements are referenced by
the same labels.

30   Figure 1 presents the basic diagram of a voice
     recognition system with constrained syntax of known
     type, for example an onboard system in a very noisy
     environment. In a single-speaker constrained syntax
     system, a non-real-time learning phase allows a given
35   speaker to record a set of acoustic references (words)
     stored in a space of references 10. The syntax 11 is
     formed of a set of phrases which represent the set of

AMENDED SHEET

possible paths or transitions between the various
words. Typically, some 300 words are recorded in the
reference space which typically form 400 000 possible
phrases of the syntax.

5

Conventionally, a voice recognition system comprises at
least three blocks as illustrated in figure 1. It
comprises a speech signal acquisition (or sound
capture) block 12, a signal processing block 13 and a
10 pattern recognition block 14. A detailed description of
this whole set of blocks according to one embodiment is
found for example in French patent application
FR 2 808 917 in the name of the applicant.

15 In a known manner, the acoustic signal processed by the
sound capture block 12 is a speech signal picked up by
an electroacoustic transducer. This signal is digitized
by sampling and chopping into a certain number of
overlapping or non-overlapping frames, of like or
20 unlike duration. In the signal processing block 13,
each frame is conventionally associated with a vector
of parameters which conveys the acoustic information
contained in the frame. There are several procedures
for determining a vector of parameters. A conventional
25 example of a procedure is that which uses the cepstral
coefficients of MFCC type (the abbreviation standing
for the expression "Mel Frequency Cepstral
Coefficient"). The block 13 makes it possible to
determine initially the spectral energy of each frame
30 in a certain number of frequency channels or windows.
For each of the frames it delivers a value of spectral
energy or spectral coefficient per frequency channel.
It then performs a compression of the spectral
coefficients obtained so as to take account of the
35 behavior of the human auditory system. Finally, it
performs a transformation of the compressed spectral
coefficients, these transformed compressed spectral

AMENDED SHEET

coefficients are the parameters of the sought-after vector of parameters.

The pattern recognition block 14 is linked to the space
5   of references 10. It compares the series of parameter vectors that emanates from the signal processing block with the references obtained during the learning phase, these references conveying the acoustic fingerprints of each word, each phoneme, more generally of each command
10 and which will be referred to generically as a "phrase" subsequently in the description. Since the pattern recognition is performed by comparison between parameter vectors, these basic parameter vectors must be at one's disposal. They are obtained in the same
15 manner as for the useful-signal frames, by calculating for each basic frame its spectral energy in a certain number of frequency channels and by using identical weighting windows.

20 On completion of the last frame, this generally corresponding to the end of a command, the comparison gives either a distance between the command tested and reference commands, the reference command exhibiting the smallest distance is recognized, i.e. a probability
25 that the series of parameter vectors belong to a string of phonemes. The algorithms conventionally used during the pattern recognition phase are in the first case of DTW type (the abbreviation standing for the expression Dynamic Time Warping) or, in the second case of HMM
30 type (the abbreviation standing for the expression Hidden Markov Models). In the case of an HMM type algorithm, the references are Gaussian functions each associated with a phoneme and not with series of parameter vectors. These Gaussian functions are
35 characterized by their center and their standard deviation. This center and this standard deviation depend on the parameters of all the frames of the

AMENDED SHEET

phoneme, that is to say the compressed spectral coefficients of all the frames of the phoneme.

The digital signals representing a recognized phase are transmitted to a device 15 which carries out the coupling with the environment, for example by displaying the recognized phrase on the head-up viewfinder of an aircraft cockpit.

As explained previously, for critical commands, the pilot can have at his disposal a validation button allowing the execution of the command. In the case where the phrase recognized is erroneous, he must generally repeat the phrase with an identical probability of error.

The method according to the invention allows automatic correction of great efficacy which is simple to implement. Its installation into a voice recognition system of the type of figure 1 is shown diagrammatically in figure 2.

According to the invention, on completion of the signal processing phase 13, the speech signal is stored (step 16) in its compressed form (set of parameter vectors also referred to as "cepstra"). As soon as a phrase is recognized, a new syntax is generated (step 17), in which the phrase recognized is no longer a possible path of the syntax. The pattern recognition phase is then repeated with the signal stored but on the new syntax. Preferably, the pattern recognition is repeated systematically to prepare another possible solution. If the pilot detects an error in the command recognized, he presses for example a specific correction button, or briefly depresses or double clicks the voice command speak/listen switch and the system prompts him with the new solution found during the repetition of the pattern

AMENDED SHEET

recognition. The above steps are repeated to generate new syntaxes which preclude all the solutions previously found. When the pilot sees the solution which actually corresponds to the phrase uttered, he
5 gives the OK through any means (button, voice, etc.).

Let us return to the example cited previously as benefiting from the invention. According to this example the pilot says "Select altitude two five five
10 zero feet". The system performs the recognition algorithms and, for example on account of ambient noise, recognizes "Select altitude two five nine zero feet". Visual feedback is given to the pilot: "SEL ALT 2 5 9 0 FT". While the speaker is engaged in reading
15 the phrase recognized, the system anticipates a possible error by automatically generating a new syntax in which the phrase recognized is deleted and by repeating the pattern recognition step.

20 Figure 3 illustrates by a simple diagram, in the case of the previous example, the modification of the syntax allowing with a pattern recognition algorithm of DTW type the search for a new phrase. The phrase uttered by the speaker according to the above example is "SEL ALT
25 2 5 5 0 FT". We assume that the phrase recognized by the first pattern recognition phase is "SEL ALT 2 5 9 0 FT". This first phase calls upon the original syntax SYNT1, in which all the combinations (or paths) are possible for the four digits to be recognized. During a
30 second pattern recognition phase, the phrase recognized is discarded from the possible combinations, thus modifying the syntactic tree as is illustrated in figure 3. A new syntax is generated which precludes the path corresponding to the solution recognized. A second
35 phase is then recognized. The pattern recognition phase may be repeated with, each time, generation of a new syntax which borrows the previous syntax but in which

AMENDED SHEET

the previously found phrase is deleted.

Thus, the new syntax is obtained by reorganizing the
earlier syntax in such a way as to particularize the
5   path corresponding to the phrase determined during the
earlier recognition step, then by eliminating this
path. This reorganization is done for example by
traversing the earlier syntax as a function of the
words of the previously recognized phrase and by
10   forming in the course of this traversal the path
specific to this phrase.

In a possible mode of operation, the pilot indicates to
the system that he wants a correction (for example by
15   briefly depressing the voice command speak/listen
switch) and as soon as a new solution is available, it
is displayed. The automatic search for a new phrase is
stopped for example when the pilot gives the OK to a
recognized phrase. In our example, it is probable that
20   right from the second pattern recognition phase, the
pilot sees "SEL ALT 2 5 5 0 FT". He can then give the
OK to the command. Insofar as numerous recognition
errors are due to confusions between words akin to one
another (for example, five-nine), the invention makes
25   it possible to correct these errors almost assuredly
with a minimum of additional workload for the pilot and
very fast on account of the anticipation regarding the
correction that the method according to the invention
may perform.
30
Furthermore, by generating a new syntax and by
repeating the pattern recognition step on the new
syntax, the complexity of the syntactic tree is not
increased. The processing algorithm can therefore
35   perform recognition with a similar lag at each
iteration, this lag being imperceptible to the pilot on
account of the anticipation of the correction.

<center>AMENDED SHEET</center>